
!!! "#\$%&' (\$"#&)

PDF temperature data logger cold chain management

—TempU02



Temperature measurement and logging easy to use,
detailed PDF reports for temperature monitoring in logistics



- | Monofunctional temperature data logger
- | 30/60/90 days logging period
- | High accuracy ($\pm 0.5\text{ }^{\circ}\text{C}$) and Sensitivity: (-20 $^{\circ}\text{C}$ to +40 $^{\circ}\text{C}$); $\pm 1.0\text{ }^{\circ}\text{C}$ (beyond this range)
- | Universal USB 2.0 communication interface
- | Temperature alarm reports with red indicator
- | LED to signal status changes (every 10 sec., in case a temperature beyond the target range was measured)
- | 10,000 measurement values can be stored
- | Easy to use with on/off button
- | No special software required for the PDF reports

Technical data



Temperature range
-30 °C to +60 °C



Logging options/period
One / 60 days
(as standard, others on request)



Logging interval
10 minutes
(as standard, others on request)



Start delay
30 minutes



Alarm delay
0 minutes



Net weight
10 g



Temperature alarm
>8 °C or <2 °C



Battery lifespan
2 years / button cell CR2032



Report generation
Automatic PDF report



Safety class
IP67 (with watertight casing)

Packaging




Individual device

Dimensions: 69 x 33 x 5 mm
Weight: 10 g



Box (50pcs.)

Dimensions: 22 x 17 x 7 cm
Weight: 0.8 kg



10x boxes

Dimensions: 36 x 25 x 37 cm
Weight: 8.5 kg

CONTACT

Casodia GmbH

 Landesberger Straße 155 | 80687 Munich | Germany

 +49 89 545 582 86

 info@casodia.com

 www.casodia.com